



Digital Flow Meter Gauges



Gauges and Digital Flow Meter to match your application

Additional models, sizes, makes, capacities and options are available.

Please contact us for information, consulting or engineering assistance.

Digital Flow Meter

| | Digital Flow Meter | Digital Low Flow Meter |
|------------------------------|---|--|
| Flow range | 3 – 30 GPM (10 – 100 l/min) | 0.3 – 3 GPM (1 to 10 l/min) |
| Typical accuracy | +/- 5% (factory calibrated) | +/- 1.5% (field calibrated) |
| Maximum Pressure Drop | 1.7 PSIG (0.12 bar) @ full flow | 2 PSIG (0.14 bar) @ full flow |
| Port size | 1" NPT | 1" NPT |
| Power | 2 x AAA batteries (included) | 2 x AAA batteries (included) |
| Electronic features | resettable batch count non resettable cumulative count | Flow rate, resettable batch count non resettable cumulative count |
| Weight | 2 lbs (0.9kg) | 2 (0.9) |

- Designed for outdoor use from 14 to + 130 deg F (-10 to +54 deg C) on fuel transfer applications diesel, gasoline, kerosene and jet fuel.
- For protection, install your digital flow meters inline after a strainer or filter.

Gauges



| | CI-20 | GV-10 | VG-30 | PG-30 | PG-60 |
|----------------------|-------------------------|-------------------------|--------------------|--------------------|--------------------|
| Type | Pressure Gauge | Vacuum Gauge | Vacuum Gauge | Pressure Gauge | Pressure Gauge |
| Range | 0-60 PSI | 0-30 "HG | 0-30 "HG | 0-30 PSI | 0-60 PSI |
| Connection | Center Back 1/8" NPT | Center Back 1/8" NPT | Bottom 1/4" NPT | Bottom 1/4" NPT | Bottom 1/4" NPT |
| Design type | Dry, color coded | Dry, color coded | Liquid filled, SS | Liquid filled, SS | Liquid filled, SS |
| Dial Diameter | 2" | 2" | 2 1/2" | 2 1/2" | 2 1/2" |
| Weight | 3.5 oz | 3.5 oz | 6 oz | 6 oz | 6 oz |

DIESEL FUEL DOCTOR